



120knurls

right hand thread
single start
76° turn
pitch 2,7mm



— gauge dimension

Excerpt from DIN 16901 series 150

Postmolding ovality dimensions can be influenced by packaging and logistics
Nominal Diameters are defined as mean of two rectangular measurements

Dimension	0-3	3-6	6-10	10-15	15-22	22-30	30-40	40-53	53-70
Tolerance	±0,15	±0,17	±0,2	±0,24	±0,28	±0,33	±0,39	±0,47	±0,58



BERICAP
GmbH & Co.
D-55257 BUDENHEIM/RHEIN
Kirchstraße 5

for internal use only		Sheet
Import No.:		1
Proj.No.	PRO-00-000311	
Art.No.	PAR-00-0000423	1 Sh.
3D-Modell No.	ENG-00-021825 d	

Tel.: +49 (0) 6139/2902-0 Fax: +49 (0) 6139/2902-182

				Tolerances unless otherwise stated: DIN 16 901 150	Surface: DIN ISO 1302 (Ra)
				Drawn	Date
				29.08.08	Spira
				Approved	

This drawing is the property of Bericap Germany.
It is confidential and must not be copied or shown to third parties.

Category **Customer drawing**

Title **Screw cap**
DS SUS 28/16 7084 SFB CSD2

d	Zeichnung aktualisiert	30.03.10	SS	Scale: 5:1 1:1	metric
c	changed name	14.09.09	SS		
b	geändert nach 09-120-B	28.08.09	FG		
a	"Gewindeschrägen" hinzugefügt.	03.02.09	FG		
Iss.	Change	Date	Name		

Master-Producthierarchy No.

Drawing No. **ENG-00-021826 d**